

TouchDown™ for PowerBar™ Bracket

» Installation Guide | Guía de Instalación | Guide d'Installation

Read Instructions Before Use

Always be aware of, and follow local plumbing codes.

Failure to follow these instructions could result in personal injury or property damage.

- 1 Slide TouchDown clamp into the open end of the PowerBar bracket.
- 1 Deslice la abrazadera TouchDown en el extremo abierto del soporte PowerBar.
- 1 Faites glisser le collier TouchDown dans l'extrémité ouverte du support PowerBar.
- 2 Load insert into the TouchDown and press into place.
- 2 Coloque el inserto en el TouchDown y presiónelo hasta que quede en su lugar.
- 2 Placez l'insert dans le TouchDown et appuyez dessus pour le mettre en place.



⚠ **WARNING:** Cancer and Reproductive Harm
⚠ **ADVERTENCIA:** Cáncer y Daños Reproductivos
⚠ **AVERTISSEMENT:** Cancer et effets néfastes sur la reproduction
www.P65Warnings.ca.gov

Safe Working Load* | Carga Segura de Trabajo* | Charge de Travail Sécuritaire*

Bracket Soporte Support		Nylon Clamps Abrazaderas de Nylon Colliers en Nylon		E84 (PVDF) Clamps Abrazaderas E84 Colliers E84	
Span	Safe load	Temp.	Safe load	Temp.	Safe load
14"	150 lbs.	-10°-130°F	70 lbs.	-10°-130°F	50 lbs.
17"	115 lbs.	131°-179°F	38 lbs.	131°-179°F	35 lbs.
21"	80 lbs.	180°-220°F	12 lbs.	180°-220°F	25 lbs.
24"	45 lbs.	220°F +	—	220°F +	—

*Safe working load = one-half failure of centrally hung load

* Carga segura de trabajo = la mitad de la carga de falla aplicada en el centro

* Charge de travail sécuritaire = la moitié de la charge de rupture suspendue au centre

Supply

Drainage

Support

Specialties

www.siouxchief.com

14940 Thunderbird Road
Kansas City, MO 64147
P 1.800.821.3944
F 1.800.758.5950

