

FLEXIBLE SUPPLY TUBES – TOILET

/// 283-T SERIES, 285-T SERIES

SPECIFICATION

Tomahawk 283-T and 285-T Flexible Supply Tubes shall be used for connecting water supply to toilet and shall meet or exceed ASME A112.18.6.

INSTALLATION

Connect to supply valve making sure nylon or brass ferrule is positioned on tube.

MATERIALS

Tube: PEX with molded head or rough brass (copper) with or without a rubber nose cone

Finish: chrome-plated or PEX

Ferrule: nylon or brass

FEATURES

- available lengths: 12", 16" and 20"

CERTIFICATIONS

ASME A112.18.6

NSF-PW-G

ASTM F876

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____




283-T24112C00




285-T2412000




283-T25112C00



Rubber Nose Cone



PEX Nose Cone



With Flat Washer

*The wetted surface of this product contacted by consumable water contains less than 0.25% of lead by weight.

Create Item Number

28A-TB1CCD

e.g. **283-T24112C00**: rough brass (copper), 3/8" O.D. tube x 7/8" w/ rubber nose cone, 12", 100/bx

CATEGORY **A**

283 = rough brass (copper)

285 = PEX

INLET x OUTLET **B**

24 = 3/8" O.D. tube X 7/8" w/ rubber nose cone

25 = 3/8" O.D. tube X 7/8" with flat washer

LENGTH **C**

12 = 12"

16 = 16"

20 = 20"

PACKAGE **D**

00 = packed 100 per box

50 = packed 50 per box



*Not all combinations available. Contact your local rep to confirm availability.