

FLEXIBLE PVC SPA HOSE with RIGID PVC HELIX

»» 900-16 SERIES

SPECIFICATION

Sioux Chief flexible PVC spa hose is manufactured to specifications from polyvinyl chloride material reinforced with rigid PVC helix. Hose provides good flexibility and is approved for use with PVC Schedule 40 fittings using PVC solvent cements and primers only. Smooth interior allows unrestricted flow. See website for chemical resistance listing.

TYPICAL APPLICATIONS

Spas, swimming pools, suction hose, hot tubs, jetted tubs, filters, vacuum discharge hose, whirlpools, or other open systems.

⚠ WARNING: Not intended for use with potable water

ATTRIBUTES

Color: White

Material: Flexible PVC with integral, rigid PVC helix

Working Temperature: -5°F (-21°C) to 150°F (66°C)

Bend Radius: 3" to 5"

WORKING PRESSURE

ID:	OD:	Working Pressure
0.5"	0.85"	100 PSI @ 70°F
0.75"	1.05"	100 PSI @ 70°F
1.0"	1.32"	100 PSI @ 70°F
1.25"	1.66"	80 PSI @ 70°F
1.50"	1.90"	65 PSI @ 70°F
2.0"	2.38"	65 PSI @ 70°F

ITEM # SUBMITTED	_____
JOB NAME	_____
LOCATION	_____
ENGINEER	_____
CONTRACTOR	_____
PO#	_____ TAG _____



Create Item Number

900-AB

e.g. **8900-16300W00101**: Flexible, white PVC spa hose, 3/4" ID, 10-ft coil

HOSE ID **A**

16200 = 1/2" ID

16300 = 3/4" ID

16400 = 1" ID

16500 = 1-1/4" ID

16600 = 1-1/2" ID

16700 = 2" ID

LENGTH* **B**

W00021 = 2-ft stick

W00101 = 10-ft coil

W00504 = 50-ft coil

W01004 = 100-ft coil

* Not all size and length combinations are available. See website to confirm product availability.