PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	ECO-1	EXTERIOR CLEANOUT	SIOUX CHIEF 834-4DNRVH FINISHLINE FLOOR CLEANOUT, CAST IRON BODY WITH NO-HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-1/2" ROUND, SCORIATED, VANDAL-RESISTANT, SPECIAL-DUTY NICKEL BRONZE RING & COVER. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3DNRVH
				4"	834-4DNRVH
				6"	834-6DNRV
	ECO-1	EXTERIOR CLEANOUT	SIOUX CHIEF 850-9i CAST IRON DOUBLE FLANGED HOUSING WITH HEAVY-DUTY SECURED SCORIATED CAST IRON COVER WITH LIFTING DEVICE AND 858-64L CLEANOUT BODY PUSH JOINT WITH 878-40 POLYPROPYLENE PLUG	–	850-9i
			PUSH-JOINT X FIP ADAPTER - 858-64L	4"	858-64L
			SLOTTED POLYPRO FLUSH PLUG - 878-40	4"	878-40
			SLOTTED POLYPRO FLUSH PLUG - 878-60	4"	878-60
	FCO-1	FLOOR CLEANOUT	SIOUX CHIEF 834-4DNR FINISHLINE FLOOR CLEANOUT, CAST IRON BODY WITH NO-HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-1/2" ROUND SCORIATED NICKEL BRONZE RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3DNR
				4"	834-4DNR
				6"	834-6DNR
	FCO-1	FLOOR CLEANOUT	SIOUX CHIEF 834-4DNQ FINISHLINE FLOOR CLEANOUT, CAST IRON BODY WITH NO-HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-5/8" SQUARE SCORIATED NICKEL BRONZE RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3DNQ
				4"	834-4DNQ
	FCO-1	FLOOR CLEANOUT	SIOUX CHIEF 834-4PNR FINISHLINE FLOOR CLEANOUT, PVC BODY WITH SCH. 40 HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-1/2" ROUND SCORIATED NICKEL BRONZE RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3PNR
				4"	834-4PNR
	FCO-1	FLOOR CLEANOUT	SIOUX CHIEF 834-4PNQ FINISHLINE FLOOR CLEANOUT, PVC BODY WITH SCH. 40 HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-5/8" SQUARE SCORIATED NICKEL BRONZE RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3PNQ
				4"	834-4PNQ
	FCOH	FLOOR CLEANOUT HEAVY DUTY	SIOUX CHIEF 834-4DNRH FINISHLINE FLOOR CLEANOUT, CAST IRON BODY WITH NO-HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE ROUND SCORIATED NICKEL BRONZE SPECIAL-DUTY RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR.	3"	834-3DNRH
				4"	834-4DNRH
	FCO-1	FLOOR CLEANOUT STAINLESS STEEL	SIOUX CHIEF 834-4SSR FINISHLINE FLOOR CLEANOUT - STAINLESS STEEL BODY WITH NO-HUB OUTLET, POLYPROPYLENE INTERNAL CLEANOUT PLUG. ADJUSTABLE 6-1/2" ROUND SCORIATED STAINLESS STEEL RING & COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	834-3SSR
				4"	834-4SSR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 833-225NR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. CLAMPING COLLAR AND ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-225NR
				3"	833-235NR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 833-23NR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. CLAMPING COLLAR AND ADJUSTABLE 6-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-22NR
				3"	833-23NR
				4"	833-24NR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 833-23NQ FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. CLAMPING COLLAR AND ADJUSTABLE 7" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-22NQ
				3"	833-23NQ
				4"	833-24NQ
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-25DNR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	832-25DNR
				3"	832-35DNR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-3DNR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 6-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	832-3DNR
				4"	832-4DNR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-3DNQ FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 7" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	832-3DNQ
				4"	832-4DNQ
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-36PNR FINISHLINE FLOOR DRAIN, PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 6-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	832-2PNR
				3"	832-36PNR
				4"	832-4PNR
	FD-1	FLOOR DRAIN	SIOUX CHIEF 832-36PNQ FINISHLINE FLOOR DRAIN, PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 7" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	832-2PNQ
				3"	832-36PNQ
				4"	832-4PNQ
	FD-1	FLOOR DRAIN HEAVY DUTY	SIOUX CHIEF 832-3DiR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 6-1/2" ROUND HEAVY-DUTY DUCTILE IRON RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	832-3DiR
				4"	832-4DiR
	FD-1	FLOOR DRAIN HEAVY DUTY	SIOUX CHIEF 833-23DiR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. CLAMPING COLLAR AND ADJUSTABLE 6-1/2" ROUND HEAVY-DUTY DUCTILE IRON RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-22DiR
				3"	833-23DiR
				4"	833-24DiR
	FD-1	FLOOR DRAIN ABOVE GRADE ON METAL DECK	SIOUX CHIEF 822-F2DNR HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. USE 822-EX3 THREADED EXTENSIONS UNDER CORING SLEEVE FOR CONCRETE POURS OF 4" OR MORE.	2"	822-F2DNR
				3"	822-F3DNR
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON METAL DECK	SIOUX CHIEF 822-F2DNQ HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 5-7/8" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. USE 822-EX3 THREADED EXTENSIONS UNDER CORING SLEEVE FOR CONCRETE POURS OF 4" OR MORE.	2"	822-F2DNQ
				3"	822-F3DNQ
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON METAL DECK	SIOUX CHIEF 822-F2PNR HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. USE 822-EX3 THREADED EXTENSIONS UNDER CORING SLEEVE FOR CONCRETE POURS OF 4" OR MORE.	2"	822-F2PNR
				3"	822-F3PNR
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON METAL DECK	SIOUX CHIEF 822-F2PNQ HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 5-7/8" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. USE 822-EX3 THREADED EXTENSIONS UNDER CORING SLEEVE FOR CONCRETE POURS OF 4" OR MORE.	2"	822-F2PNQ
				3"	822-F3PNQ
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON WOOD DECK	SIOUX CHIEF 822-2DNR HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. USE 822-EX3 THREADED EXTENSIONS AS NEEDED.	2"	822-2DNR
				3"	822-3DNR
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER HEAD ADAPTER TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON WOOD DECK	SIOUX CHIEF 822-2DNQ HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND CAST IRON BODY WITH NO-HUB OUTLET. ADJUSTABLE 5-7/8" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. USE 822-EX3 THREADED EXTENSIONS AS NEEDED	2"	822-2DNQ
				3"	822-3DNQ
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER HEAD ADAPTER TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON WOOD DECK	SIOUX CHIEF 822-2PNR HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE RING & GRATE. USE 822-EX3 THREADED EXTENSIONS AS NEEDED	2"	822-2PNR
				3"	822-3PNR
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-1	FLOOR DRAIN ABOVE GRADE ON WOOD DECK	SIOUX CHIEF 822-2PNQ HALO FLOOR DRAIN WITH STAINLESS STEEL MOUNTING FLANGE AND PVC BODY WITH SCH. 40 HUB OUTLET. ADJUSTABLE 5-7/8" SQUARE HEEL-RESISTANT NICKEL BRONZE RING & GRATE. USE 822-EX3 THREADED EXTENSIONS AS NEEDED	2"	822-2PNQ
				3"	822-3PNQ
			STACKABLE IRON ACME THREAD EXTENSIONS. USE UNDER CORING SLEEVE TO EXTEND UP TO 4".	–	822-EX3
	FD-2	FLOOR DRAIN STAINLESS STEEL	SIOUX CHIEF 832-3SSRM FINISHLINE FLOOR DRAIN, STAINLESS STEEL BODY WITH NO-HUB OUTLET. ADJUSTABLE 6-1/2" ROUND, HEEL-RESISTANT, STAINLESS STEEL RING & GRATE. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	3"	832-3SSRM
				4"	832-4SSRM
	FD-2	FLOOR DRAIN EQUIPMENT ROOM	SIOUX CHIEF 832-49DF FINISHLINE CAST IRON DRAIN BODY WITH NO-HUB OUTLET. USE 832-SD9 9" ROUND, ADJUSTABLE, LOOSE-SET HEAVY-DUTY, HEEL-RESISTANT, DUCTILE IRON GRATE. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	4"	832-49DF
				6"	832-6DF
			9" ROUND, ADJUSTABLE, HEAVY-DUTY, HEEL-RESISTANT, DUCTILE IRON GRATE.	–	832-SD9

PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	FD-2	FLOOR DRAIN EQUIPMENT ROOM	SIOUX CHIEF 860-4PZ2S FAT MAX LARGE CAPACITY PVC FLOOR DRAIN WITH ANCHOR FLANGE, 9-3/4" ROUND STAINLESS STEEL OPEN HALF GRATE AND SEDIMENT BUCKET	2"	860-2PZ2S
				3"	860-3PZ2S
				4"	860-4PZ2S
				6"	860-6PZ2S
	FD-2	FLOOR DRAIN	SIOUX CHIEF 860-R224iB FATMAX FLOOR DRAIN, CAST IRON BODY WITH SEEPAGE FLANGE, MEMBRANE FLASHING CLAMP, SEDIMENT BUCKET AND NO-HUB OUTLET. 12" ROUND, LOOSE-SET, HEAVY-DUTY, DUCTILE IRON GRATE. PROVIDE TRAP PRIMER PORT IF TRAP PRIMER IS PROVIDED IN DRAWINGS.	2"	860-R222iB
				3"	860-R223iB
				4"	860-R224iB
				6"	860-R226iB
				8"	860-R228iB
	FD-2	FLOOR DRAIN	SIOUX CHIEF 868-R624i FATMAX FLOOR DRAIN, CAST IRON BODY WITH SEEPAGE FLANGE, MEMBRANE FLASHING CLAMP AND NO-HUB OUTLET. 16" ROUND, LOOSE-SET, HEAVY-DUTY, DUCTILE IRON GRATE. PROVIDE TRAP PRIMER PORT IF TRAP PRIMER IS PROVIDED IN DRAWINGS.	3"	868-R623i
				4"	868-R624i
				6"	868-R626i
				8"	868-R628i
	HD-1	HUB DRAIN	SIOUX CHIEF 833-23DF FINISHLINE CAST IRON DRAIN BODY WITH CLAMPING COLLAR AND ADJUSTABLE CORING SLEEVE AND TEMPORARY COVER. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL 832-4HHD ADJUSTABLE HUB FINISH FIXTURE WITH 832-UM STAINLESS STEEL DEBRIS BASKET	2"	833-22DF
				3"	833-23DF
				4"	833-24DF
			ADJUSTABLE HUB DRAIN FIXTURE 832-4HHD	–	832-4HHD
			STAINLESS STEEL MESH DEBRIS BASKET 832-UM	–	832-UM
	FFD-1	FUNNEL FLOOR DRAIN	SIOUX CHIEF 833-225NR FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET. ABS CLAMPING COLLAR, CORING SLEEVE AND HEAD ADAPTER. ADJUSTABLE 5-1/2" ROUND HEEL-RESISTANT NICKEL BRONZE STRAINER. ADJUSTABLE BEFORE AND AFTER POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR. PROVIDE WITH 863-FA FUNNEL	2"	833-225NR
				3"	833-235NR
				4"	833-24NR
			CONDENSATE FUNNEL 863-FA	–	863-FA
	RRFD-1	RAISED RIM FLOOR DRAIN	SIOUX CHIEF 833-23DNRE FINISHLINE FLOOR DRAIN, CAST IRON BODY WITH NO-HUB OUTLET, CLAMPING COLLAR, CORING SLEEVE AND HEAD ADAPTER. ADJUSTABLE 6-7/8" ROUND NICKEL BRONZE GRATE WITH 1-7/8" RAISED RIM. ADJUSTABLE BEFORE AND AFTER CONCRETE POUR. INSTALL CONSTRUCTION COVER FLUSH WITH CONCRETE POUR	2"	833-22DNRE
				3"	833-23DNRE
				4"	833-24DNRE
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2326N2BC, 6" DEEP CAST IRON BODY WITH NO-HUB OUTLET. ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMPING COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE.	2"	861-QF2226N2BC
				3"	861-QF2326N2BC
				4"	861-QF2426N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2328N2BC, 8" DEEP CAST IRON BODY WITH NO-HUB OUTLET. ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMPING COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE.	2"	861-QF2228N2BC
				3"	861-QF2328N2BC
				4"	861-QF2428N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2321N2BC, 10" DEEP CAST IRON BODY WITH NO-HUB OUTLET. ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, CLAMP COLLAR, ALUMINUM SEDIMENT BUCKET, AND 12" SQUARE NICKEL BRONZE RIM AND HALF GRATE.	2"	861-QF2221N2BC
				3"	861-QF2321N2BC
				4"	861-QF2421N2BC
	FS-1	FLOOR SINK	SIOUX CHIEF 861-QF2386A, 6" DEEP CAST IRON BODY WITH NO-HUB OUTLET. ACID RESISTING ENAMELED INTERIOR, ANCHOR FLANGE WITH SEEPAGE HOLES, ALUMINUM SEDIMENT BUCKET, AND 8" SQUARE ACID RESISTING ENAMELED CAST IRON GRATE.	2"	861-QF2286A
				3"	861-QF2386A
				4"	861-QF2486A
	FS-1	FLOOR SINK	SIOUX CHIEF 861-3P2W SQUAREMAX 6" DEEP, 12" X 12" PVC SQUARE FLOOR SINK WITH ANCHOR FLANGE AND SCH. 40 HUB OUTLET. SQUARE PVC HALF GRATE AND REMOVABLE, STAINLESS STEEL MESH DEBRIS BASKET.	2"	861-2P2W
				3"	861-3P2W
				4"	861-4P2W
				6"	861-6P2W
	FS-1	FLOOR SINK	SIOUX CHIEF 861-SQ2428, 8" DEEP, 12" X 12" STAINLESS STEEL SQUARE FLOOR SINK WITH NO-HUB OUTLET. 14-GAUGE TYPE 304 BODY WITH LOW-PROFILE RIM. PROVIDE WITH GRATE AND DEBRIS BASKET.	4"	861-SQ2428
			861-GKQ2F 304SS 12" X 12" SQUARE FULL GRATE FOR 861-SQ2428	–	861-GKQ2F
			861-BKQ2 304SS REMOVABLE DEBRIS BASKET FOR 861-SQ2428	–	861-BKQ2
	FS-1	FLOOR SINK	SIOUX CHIEF 860-3P2W FATMAX 6" DEEP, 9-3/4" GRAY PVC ROUND FLOOR SINK WITH ANCHOR FLANGE AND SCH. 40 HUB OUTLET. ROUND PVC HALF GRATE AND REMOVABLE, STAINLESS STEEL MESH DEBRIS BASKET.	2"	860-2P2W
				3"	860-3P2W
				4"	860-4P2W
				6"	860-6P2W
	BWV	BACKWATER VALVE	SIOUX CHIEF PROCHECK BACKWATER VALVE WITH PVC BODY, CARRIER AND FLAPPER. FLAPPER ALLOW UNRESTRICTED, UNIDIRECTIONAL FLOW. VALVE DESIGN TO BE ADAPTABLE TO SHALLOW OR DEEP-BURY INSTALLATIONS.	3"	869-S3P
				4"	869-S4P
			BACKWATER VALVE WITH PVC BODY, LID AND FLAPPER - 869-2P	2"	869-2P
			BACKWATER VALVE WITH PVC BODY, LID AND FLAPPER - 869-6P	6"	869-6P
	ORD-1	OVERFLOW ROOF DRAIN	SIOUX CHIEF # 868-524SCEW, 15" DIAMETER CAST IRON OVERFLOW ROOF DRAIN, FLASHING CLAMP, 2" HIGH EXTERNAL WATER DAM, SUMP RECEIVER, UNDERDECK CLAMP, NO HUB OUTLET AND SECURED CAST IRON DOME. ADJUSTABLE THREADED EXTENSION TO MATCH INSULATION THICKNESS.	3"	868-523SCEW
				4"	868-524SCEW
				6"	868-526SCEW
				8"	868-528SCEW
	RD-1	ROOF DRAIN	SIOUX CHIEF # 868-524SCE, 15" DIAMETER CAST IRON ROOF DRAIN, GRAVEL GUARD FLASHING CLAMP, SUMP RECEIVER, UNDERDECK CLAMP, NO HUB OUTLET AND SECURED CAST IRON DOME. ADJUSTABLE THREADED EXTENSION TO MATCH INSULATION THICKNESS.	3"	868-523SCE
				4"	868-524SCE
				6"	868-526SCE
				8"	868-528SCE
	ORD-2	OVERFLOW ROOF DRAIN	SIOUX CHIEF 868-2010USW CAST IRON 20" DIAMETER OVERFLOW ROOF DRAIN WITH FLASHING CLAMP, 2" EXTERNAL WATER DAM AND CAST IRON LOCKING DOME. PROVIDE SUMP RECEIVER, UNDER-DECK CLAMP	10"	868-2010USW
				12"	868-2012USW
	RD-2	ROOF DRAIN	SIOUX CHIEF 868-2010US CAST IRON 20" DIAMETER ROOF DRAIN WITH GRAVEL GUARD FLASHING CLAMP AND CAST IRON LOCKING DOME. PROVIDE SUMP RECEIVER, UNDER-DECK CLAMP.	10"	868-2010US
				12"	868-2012US
	OD-3	OVERFLOW ROOF DRAIN	SIOUX CHIEF 868-i3W CAST IRON 11" DIAMETER ROOF DRAIN WITH FLASHING CLAMP AND 2" HIGH EXTERNAL WATER DAM, SECURED POLYPROPYLENE DOME. PROVIDE SUMP RECEIVER, UNDERDECK CLAMP AND EXTENSION COLLAR KIT.	3"	868-i3WUES
				4"	868-i4WUES
				6"	868-i6WUES
	RD-3	ROOF DRAIN	SIOUX CHIEF 868-i3 CAST IRON 11" DIAMETER ROOF DRAIN WITH GRAVEL GUARD FLASHING CLAMP, SECURED POLYPROPYLENE DOME. PROVIDE SUMP RECEIVER, UNDERDECK CLAMP AND EXTENSION COLLAR KIT.	3"	868-i3UES
				4"	868-i4UES
				6"	868-i6UES
	RD-3	ROOF DRAIN	SIOUX CHIEF 868-P3UES PVC 11" DIAMETER ROOF DRAIN WITH GRAVEL GUARD FLASHING CLAMP, SECURED POLYPROPYLENE DOME. PROVIDE SUMP RECEIVER, UNDERDECK CLAMP AND EXTENSION COLLAR KIT.	3"	868-P3UES
				4"	868-P4UES
				6"	868-P6UES
	RD-3	ROOF DRAIN	SIOUX CHIEF 867-P3 ROOF DRAIN WITH PVC BODY, FLASHING COLLAR WITH SEEPAGE OPENINGS AND SECURED U.V. RESISTANT POLYPROPYLENE DOME. 3" SCH. 40 HUB OUTLET	3"	867-P3
				4"	867-P4
	PD-1	PLANTER DRAIN	SIOUX CHIEF 867-L3PP MULTI-LEVEL PLANTER DRAIN, PVC BODY, FLASHING COLLAR WITH SEEPAGE OPENINGS AND SECURED U.V. RESISTANT POLYPROPYLENE DOME WITH STAINLESS STEEL MESH SCREEN AND 4" PERFORATED ADJUSTABLE LENGTH STANDPIPE. 3" SCH. 40 HUB OUTLET	3"	867-L3PP
				4"	867-L4PP
	PD-2	PLANTER DRAIN	SIOUX CHIEF 867-P3P PLANTER DRAIN, PVC BODY, FLASHING COLLAR WITH SEEPAGE OPENINGS AND SECURED U.V. RESISTANT POLYPROPYLENE DOME WITH STAINLESS STEEL MESH SCREEN AND 4" SCH. 40 HUB OUTLET	3"	867-P3P
				4"	867-P4P
	DSC-1	DOWNSPOUT COVER	SIOUX CHIEF 868-N4S ROUND FABRICATED STAINLESS STEEL FRAME WITH FABRICATED SECURED PERFORATED STAINLESS STEEL HINGED COVER	3"	868-N3S
				4"	868-N4S
				6"	868-N6S
				8"	868-N8S
	DSN-1	DOWNSPOUT NOZZLE	SIOUX CHIEF 868-N4H CAST NICKEL BRONZE DOWNSPOUT NOZZLE WITH NO-HUB CONNECTION AND FLANGED TO SECURE NOZZLE TO WALL. PROVIDE 868-NS4 STAINLESS STEEL SCREEN	3"	868-N3H
				4"	868-N4H
				6"	868-N6H
				8"	868-N8H
			STAINLESS STEEL MESH PROTECTION SCREEN FOR DOWNSPOUT NOZZLE	3"	868-NS3
				4"	868-NS4
				6"	868-NS6
				8"	868-NS8
	SD-1	SCUPPER DRAIN	SIOUX CHIEF 868-S3A CAST IRON SCUPPER DRAIN WITH ALUMINUM FLASHING CLAMP AND SECURED, ALUMINUM, ANGLED GRATE. FIP THREAD CONNECTION	3"	868-S3A
				4"	868-S4A
				6"	868-S6A
	SD-1	SCUPPER DRAIN	SIOUX CHIEF 868-S3F CAST IRON SCUPPER DRAIN WITH ALUMINUM FLASHING CLAMP AND SECURED, ALUMINUM, FLUSH GRATE. FIP THREAD CONNECTION	3"	868-S3F
				4"	868-S4F
				6"	868-S6F

PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	TD-1	TRENCH DRAIN CLASS A15 (DECORATIVE)	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/OUTLET, 865-EG STAINLESS STEEL EDGE GUARDS AND 865-GSA SLOTTED STAINLESS STEEL, LOAD CLASS A, ADA COMPLIANT HEEL-RESISTANT GRATE.	4"	865-S1
				4"	865-S2
			STAINLESS STEEL EDGE GUARDS - 36" - PAIR	–	865-EG
			DIAG-SLOT SS TRENCH DRAIN GRATE - ADA / HEEL-RESISTANT	–	865-GSA
			END CAP / END OUTLET	4"	865-EO
	TD-1	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/OUTLET, 865-F DUCTILE IRON GRATE FRAME AND 865-GIS HEAVY-DUTY SLOTTED DUCTILE IRON, LOAD CLASS D, GRATE.	4"	865-S1
				4"	865-S2
			HEAVY-DUTY DUCTILE IRON GRATE FRAME - 36"	–	865-F
			HEAVY-DUTY SLOTTED DUCTILE IRON TRENCH DRAIN GRATE - CLASS D400	–	865-GIS
			END CAP / END OUTLET	4"	865-EO
	TD-1	TRENCH DRAIN CLASS A15	SIOUX CHIEF 865-S1 FASTTRACK HDPE SLOPED TRENCH DRAIN, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-EO CAP/OUTLET AND 865-GHC SLOTTED REINFORCED POLYPRO, LOAD CLASS A, HEEL-RESISTANT GRATE.	4"	865-S1
				4"	865-S2
			SLOTTED REINFORCED POLYPRO TRENCH DRAIN GRATE - ADA / HEEL-RESIST.	–	865-GHC
			END CAP / END OUTLET	4"	865-EO
	TD-2	TRENCH DRAIN CLASS A15 (DECORATIVE) FOR DEPTH-RESTRICTED	SIOUX CHIEF 865-NS1 FASTTRACK HDPE SHALLOW TRENCH DRAIN, 3-3/4" TALL, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-NSC END CAPS, 865-EG STAINLESS STEEL EDGE GUARDS AND 865-GSA DIAGONAL SLOTTED STAINLESS STEEL, LOAD CLASS A, ADA COMPLIANT HEEL PROOF GRATE	4"	865-NS1
			STAINLESS STEEL EDGE GUARDS - 36" - PAIR	–	865-EG
			DIAG-SLOT SS TRENCH DRAIN GRATE - ADA / HEEL-RESISTANT	–	865-GSA
			END CAP	4"	865-NSC
	TD-2	TRENCH DRAIN CLASS D400 FOR DEPTH-RESTRICTED	SIOUX CHIEF 865-NS1 FASTTRACK HDPE SHALLOW TRENCH DRAIN, 3-3/4" TALL, 6" WIDE GRATE, 4.5" CHANNEL I.D. WITH 4" NO-HUB OUTLET. USE 865-NSC END CAPS, 865-F DUCTILE IRON GRATE FRAME AND 865-GIS HEAVY-DUTY SLOTTED DUCTILE IRON, LOAD CLASS D, GRATE.	4"	865-NS1
			HEAVY-DUTY DUCTILE IRON GRATE FRAME - 36"	–	865-F
			HEAVY-DUTY SLOTTED DUCTILE IRON TRENCH DRAIN GRATE - CLASS D400	–	865-GIS
			END CAP	–	865-NSC
	TD-2	TRENCH DRAIN CLASS F900 FOR DEPTH-RESTRICTED	SIOUX CHIEF 865-HLP4N00F1M HYDROLINE ALUMINUM, LOW-PROFILE, TRENCH DRAIN. 1-3/16" TALL, 5-1/4" WIDE. FOR HEAVY-DUTY, CLASS F900 APPLICATIONS. USE WITH 865-HLP4AB 4" NO HUB BOTTOM OUTLET, 865-HLPEC END CAP, AND 865-HLPISC INSTALLATION BRACKET.	4"	865-HLP4N00F1M
	TD-3	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-M4N10 HYDROTEC MAXI 100 REINFORCED CONCRETE CHANNEL TRENCH DRAIN. 6" WIDE GRATE, 4" CHANNEL I.D. WITH INTEGRAL IRON EDGE RAIL. USE 865-M4DIDL DUCTILE IRON, ADA, CLASS D400 GRATE, 865-4BK INSTALLATION BRACKET, 865-4EC END CAP, 865-4OC END OUTLET. USE 865-M4N10B FOR BOTTOM OUTLET CHANNEL. REFER TO PLANS FOR OUTLET LOCATION.	4"	865-M4N10
				–	865-M4DIDL
	TD-3	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-M6N00DA HYDROTEC MAXI 150 REINFORCED CONCRETE CHANNEL TRENCH DRAIN. 8" WIDE GRATE, 6" CHANNEL I.D. WITH INTEGRAL IRON EDGE RAIL AND SLOTTED, DUCTILE IRON, ADA, CLASS D400 GRATE. USE 865-6BK INSTALLATION BRACKET, 865-6UC END CAP/OUTLET. USE 865-M6N00BDA FOR BOTTOM OUTLET CHANNEL. REFER TO PLANS FOR OUTLET LOCATION.	6"	865-M6N00DA
	TD-3	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-M8N00DA HYDROTEC MAXI 200 REINFORCED CONCRETE CHANNEL TRENCH DRAIN. 10" WIDE GRATE, 8" CHANNEL I.D. WITH INTEGRAL IRON EDGE RAIL AND SLOTTED, DUCTILE IRON, ADA, CLASS D400 GRATE. USE 865-8BK INSTALLATION BRACKET, 865-8ECD END CAP, 865-8OCD END OUTLET. USE 865-M8N00BDA FOR BOTTOM OUTLET CHANNEL. REFER TO PLANS FOR OUTLET LOCATION.	6"	865-M8N00DA
	TD-3	TRENCH DRAIN CLASS E600	SIOUX CHIEF 865-M12PN00EA HYDROTEC MAXI 300 REINFORCED CONCRETE CHANNEL TRENCH DRAIN. 15" WIDE GRATE, 12" CHANNEL I.D. WITH INTEGRAL IRON EDGE RAIL, 'ANTI-RATTLE' GRATE INSERT AND SLOTTED, DUCTILE IRON, ADA, CLASS E600 GRATE WITH 'F-1' LOCKING MECHANISM. USE 865-12ECD END CAP, 865-12OCD END OUTLET. USE 865-M12PN00BEA FOR BOTTOM OUTLET CHANNEL. REFER TO PLANS FOR OUTLET LOCATION.	8"	865-M12PN00EA
	TD-3	TRENCH DRAIN CLASS F900	SIOUX CHIEF 865-M16PN00FA HYDROTEC MAXI 400 REINFORCED CONCRETE CHANNEL TRENCH DRAIN. 19" WIDE GRATE, 16" CHANNEL I.D. WITH INTEGRAL IRON EDGE RAIL, 'ANTI-RATTLE' GRATE INSERT AND SLOTTED, DUCTILE IRON, ADA, CLASS F900 GRATE WITH 'F-1' LOCKING MECHANISM. USE 865-16ECD END CAP, 865-16OCD END OUTLET. USE 865-M16PN00BFA FOR BOTTOM OUTLET CHANNEL. REFER TO PLANS FOR OUTLET LOCATION.	8"	865-M16PN00FA
	TD-4	TRENCH DRAIN CLASS F900	SIOUX CHIEF 865-HB6ADA00FA HYDROBLOCK 6" WIDE, ONE-PIECE, TYPE-I, DUCTILE IRON TRENCH DRAIN WITH INTEGRAL, 'ANTI-TORQUE' GASKETED JOINTS. ADA, LOAD CLASS F900. USE 865-HB6EC SOCKET END CAP, 865-HB6OC SPIGOT END CAP. USE 865-HB6ADA005FA ACCESS SECTION AT BEGINNING OF RUN, AND EVERY 50FT. USE 865-HB6ADA005BFA FOR BOTTOM OUTLET SECTION. REFER TO PLANS FOR OUTLET LOCATION.	6"	865-HB6ADA00FA
	TD-4	TRENCH DRAIN CLASS F900	SIOUX CHIEF 865-HB8ADA00FA HYDROBLOCK 8" WIDE, ONE-PIECE, TYPE-I, DUCTILE IRON TRENCH DRAIN WITH INTEGRAL, 'ANTI-TORQUE' GASKETED JOINTS. ADA, LOAD CLASS F900. USE 865-HB8EC SOCKET END CAP, 865-HB8OC SPIGOT END CAP. USE 865-HB8ADA005FA ACCESS SECTION AT BEGINNING OF RUN, AND EVERY 50FT. USE 865-HB8ADA005BFA FOR BOTTOM OUTLET SECTION. REFER TO PLANS FOR OUTLET LOCATION.	8"	865-HB8ADA00FA
	TD-4	TRENCH DRAIN CLASS F900	SIOUX CHIEF 865-HB12ADA00FA HYDROBLOCK 12" WIDE, ONE-PIECE, TYPE-I, DUCTILE IRON TRENCH DRAIN WITH INTEGRAL, 'ANTI-TORQUE' GASKETED JOINTS. ADA, LOAD CLASS F900. USE 865-HB12EC SOCKET END CAP, 865-HB12OC SPIGOT END CAP. USE 865-HB12ADA005FA ACCESS SECTION AT BEGINNING OF RUN, AND EVERY 50FT. USE 865-HB12ADA005BFA FOR BOTTOM OUTLET SECTION. REFER TO PLANS FOR OUTLET LOCATION.	10"	865-HB12ADA00FA
	TD-5	TRENCH DRAIN CLASS D400	SIOUX CHIEF 865-TNDS LARGE-CAPACITY FASTTRACK 12" WIDE, HDPE CHANNEL TRENCH DRAIN. 15" WIDE GRATE, 12" CHANNEL I.D. WITH IRON EDGE RAIL AND SLOTTED, DUCTILE IRON, CLASS D400 SECURED GRATE. INTEGRAL 8" AND 10" BOTTOM OUTLET FOR OPTIONAL CONNECTION. USE 865-TEC END CAP, 865-TEO END OUTLET. REFER TO PLANS FOR OUTLET LOCATION.	8" OR 10"	865-TNDS
	SH-1	LINEAR SHOWER DRAIN	SHOWER PAN DRAIN WITH 30" LINEAR HEAD - STAMPED STAINLESS STEEL SQUARE HOLE STRAINER	2"	823-TX30SP
	SH-2	SHOWER DRAIN	SIOUX CHIEF 825-27P SHOWER MODULE DRAIN WITH STAINLESS STEEL SNAP ON STRAINER	2"	825-27P
	SH-2	SHOWER DRAIN	FIELD-TILED FLOOR WITH SIOUX CHIEF 821-T200PCQ SQUARE TILE COMPATIBLE SHOWER DRAIN WITH PVC BODY, REVERSABLE COLLAR, AND 4-1/2" SQUARE POLISHED STAINLESS STEEL STRAINER	2"	821-T200PCQ
	FSTD-1	FREESTANDING TUB DRAIN	SIOUX CHIEF 819-2P PVC FREESTANDING TUB DRAIN KIT. INCLUDES DRAIN BODY, TEST PLUG, TAILPEICE AND TAILPIECE GASKET	2"	819-2P
		URINAL CARRIER	PLATE-TYPE URINAL CARRIER	–	837-7D
		WATER CLOSET CARRIER	SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - LEFT-HAND - NO-HUB	4"	837-HSLT
			SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - RIGHT-HAND - NO-HUB	4"	837-HSRT
			DOUBLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - BACK-TO-BACK - NO-HUB	4"	837-HSDT
			TILING FRAME FOR WATER CLOSET CARRIER	–	837-TF
		WATER CLOSET CARRIER	SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - LEFT-HAND - PVC WASTE FITTING	4"	837-PHSLT
			SINGLE ADJUSTABLE HORIZONTAL WATER CLOSET CARRIER RATED FOR 500LB - RIGHT-HAND - PVC WASTE FITTING	4"	837-PHSRT
			TILING FRAME FOR WATER CLOSET CARRIER	–	837-TF
		LAVATORY CARRIER	ADJUSTABLE, CONCEALED-ARM LAVATORY CARRIER WITH 18" ARMS	–	837-7CA18
		LAVATORY CARRIER	CONCEALED-ARM LAVATORY CARRIER WITH 18" ARMS	–	837-7C18
		WATER COOLER CARRIER	PLATE-TYPE WATER COOLER CARRIER - SIDE x SIDE - SINGLE PLATE	–	837-7P2
	TP-1	TRAP SEAL PROTECTION DEVICE	SIOUX CHIEF 835-2 TRAPSHIELD BARRIER TYPE TRAP SEAL DEVICE, COMPLIES WITH ASSE 1072 AF-GW	2"	835-2
				3"	835-3
				4"	835-4
	TP-1	TRAP PRIMER TAILPIECE	SIOUX CHIEF 213-092 GRAVITY FEED LAVATORY SINK TAILPIECE TRAP PRIMER. 1/2" NOMINAL BRANCH CONNECTION. COMPLIES WITH ASSE 1044.	1-1/2"	200-092
				1-1/4"	213-096

PRODUCT	PLAN MARK	FIXTURE	DESCRIPTION	WASTE SIZE	MODEL NO.
	TP-1	PRESSURE ACTIVATED TRAP PRIMER	SIOUX CHIEF 695-01 PRIMEPERFECT MECHANICAL TRAP PRIMER. 1/2" FIP INLET X 1/2" MIP OUTLET WITH INTEGRAL VACUUM BREAKER. INSTALL VALVE A MINIMUM OF 18" ABOVE FINISHED FLOOR OR ACCESSIBLE IN THE CEILING. USE 695-Y52 SPLITTER AND 695-D432F DISTRIBUTOR AS NEEDED	–	695-01
			WYE SPLITTER - 1/2" FIP X 1/2" MIP (2)	–	695-Y52
			DISTRIBUTOR - 1/2" FIP X 1/2" FIP (4)	–	695-D432F
	TP-1	ELECTRONIC TRAP PRIMER	SIOUX CHIEF 695-ES01 ELECTRONIC TRAP PRIMER WITH 1/2"" INLET AND 1/2"" OUTLET, SOLENOID VALVE ACTUATOR, VACUUM BREAKER HOLES AND CONTROL PANEL WITH INTEGRAL TIMER. INSTALL THE VALVE AND CONTROL PANEL ABOVE CEILING. ELECTRICAL REQUIREMENTS: 120V 1PH AT 1 FLA	–	695-ES01
			WYE SPLITTER - 1/2" FIP X 1/2" MIP (2)	–	695-Y52
	ETP-1	ELECTRONIC TRAP PRIMER SURFACE MOUNT	SIOUX CHIEF 695-ES05 WITH 1/2" INLET AND OUTLET, SOLENOID VALVE ACTUATOR, INTEGRAL VACUUM BREAKER AND CONTROL PANEL WITH INTEGRAL TIMER. TRAP PRIMER SHALL BE MOUNTED IN STEEL ACCESS BOX. ELECTRICAL REQUIREMENT - CONNECT UNIT TO 120V AC SUPPLY.	–	695-ES05
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 10 PORTS	–	695-ES10
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 15 PORTS	–	695-ES15
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 20 PORTS	–	695-ES20
			ELECTRONIC TRAP PRIMER SURFACE MOUNT BOX 30 PORTS	–	695-ES30
	ETP-1	ELECTRONIC TRAP PRIMER RECESSED BOX	SIOUX CHIEF 695-ER05 WITH 1/2" INLET AND OUTLET, SOLENOID VALVE ACTUATOR, INTEGRAL VACUUM BREAKER, CONTROL PANEL, INTEGRAL TIMER. ELECTRICAL REQUIREMENT - CONNECT UNIT TO 120V AC SUPPLY.	–	695-ER05
			ELECTRONIC TRAP PRIMER RECESSED BOX 10 PORTS	–	695-ER10
			ELECTRONIC TRAP PRIMER RECESSED BOX 15 PORTS	–	695-ER15
			ELECTRONIC TRAP PRIMER RECESSED BOX 20 PORTS	–	695-ER20
			ELECTRONIC TRAP PRIMER RECESSED BOX 30 PORTS	–	695-ER30
			14" X 14" STAINLESS STEEL ACCESS COVER	–	971-1414
	CD-1	CONDENSATE DRAIN TAILPIECE	SIOUX CHIEF 206-066 LONGBRANCH CHROME PLATED BRASS 1-1/2" TAILPIECE WITH 1/2" NOMINAL BRANCH TO DRAIN CONDENSATE.	1-1/2"	206-066
	CDB-1	CONDENSATE DRAIN BOX	SIOUX CHIEF 696-3F OXBOX DRAIN BOX WITH 2" WASTE OUTLET, 696-CF SECONDARY DRAINAGE FUNNEL AND 696-SC SOLID FRAME INSERT. USED TO DRAIN CONDENSATE IN THE WALL INSTEAD OF INTO A FLOOR DRAIN.	2"	696-3F
			CONDENSATE DRAINAGE FUNNEL	–	696-CF
			REMOVABLE SOLID COVER	–	696-SC
			REMOVABLE LOUVERED COVER	–	696-LC
			FRAME EXTENSION 1/2" FOR THICKER WALLS	–	696-EX
			FIRE-RATED BOX	2"	696R3
	WCO	WALL CLEANOUT	CAST IRON CLEANOUT TEE WITH NO-HUB CONNECTION AND SLOTTED/TAPPED BRASS PLUG.	3"	853-T23i
				4"	853-T24i
				6"	853-T26i
				8"	853-T28i
			CAST IRON CLEANOUT FERRULE WITH NO-HUB CONNECTION AND SLOTTED/TAPPED BRASS PLUG.	3"	853-F23i
				4"	853-F24i
				6"	853-F26i
			SIOUX CHIEF 873-6 COVER KIT 6" STAINLESS STEEL COVER AND STAINLESS STEEL SCREW. PRODIVDE 8" COVER OR 10" COVER FOR LARGER SIZE PLUGS.	–	873-6
				–	873-8
				–	873-10
	WMB-1	WASHING MACHINE OUTLET BOX	SIOUX CHIEF 696-G2313MF OXBOX WASHING MACHINE BOX, 1/2" MIP/SWEAT INLET CONNECTIONS, QUARTER TURN VALVES WITH ARRESTERS AND 3/4" MALE HOSE THREAD OUTLET, AND 2" DRAIN OUTLET. INCLUDES STEEL BOX CLIP. USE 696RG2313MF WHEN INSTALLED IN FIRE-RATED WALLS.	2"	696-G2313MF
					696RG2313MF
	IM-1	ICE MAKER OUTLET BOX	SIOUX CHIEF 696-G1010MF OXBOX ICE MAKER BOX, QUARTER-TURN VALVE WITH ARRESTER WITH 1/2" MIP/SWEAT CONNECTION, 1/4" O.D. COMPRESSION OUTLET. VALVES COMPLY WITH ASME A112.18.1. USE 696RG1010MF WHEN INSTALLED IN FIRE-RATED WALLS.	–	696-G1010MF
					696RG1010MF
	LB-1	LAVATORY OUTLET BOX	SIOUX CHIEF 696-G2011MF OXBOX LAVATORY OUTLET BOX, QUARTER-TURN VALVES WITH ARRESTERS WITH 1/2" MIP/SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. VALVES COMPLY WITH ASME A112.18.1. MOUNT BOTTOM OF LAVATORY OUTLET BOX EVEN WITH P-TRAP WASTE ARM. USE 696-EX FRAME EXTENSION FOR THICKER WALLS. USE 696RG2011MF WHEN INSTALLED IN FIRE-RATED WALLS.	–	696-G2011MF
					696RG2011MF
	KB-1	KITCHEN SUPPLY OUTLET BOX	SIOUX CHIEF 696-G3021MR KITCHEN SUPPLY OUTLET BOX, QUARTER-TURN VALVES WITH ARRESTERS WITH 1/2" MIP/SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. THE THIRD VALVE IS FOR DISHWASHER HOT WATER. VALVES COMPLY WITH ASME A112.18.1. MOUNT BOTTOM OF LAVATORY OUTLET BOX EVEN WITH P-TRAP WASTE ARM. USE 696-1F FRAME. USE 696RG3021MF WHEN INSTALLED IN FIRE-RATED WALLS.	–	696-G3021MR
					696RG3021MR
	WSP-1	LAVATORY WATER SUPPLY OUTLET PANEL	SIOUX CHIEF 698-A11-MR OMNIPANEL LAVATORY WATER SUPPLY OUTLET PANEL. QUARTER-TURN VALVES WITH 1/2" MIP/SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. VALVES COMPLY WITH ASME A112.18.1. INTEGRAL, ELASTOMERIC PORT SEALS AROUND WASTE ARM PENETRATION. 698-RF FINISH KIT INCLUDES FINISH FRAME AND OPTIONAL FRAME EXTENSION FOR THICKER WALLS. USE 698RA11-MR WHEN INSTALLED IN FIRE-RATED WALLS.	–	698-A11-MR
					698RA11-MR
	WSP-1	WATER SUPPLY OUTLET PLATE	SIOUX CHIEF 699-A1-MR PROPLATE WATER SUPPLY OUTLET PLATE. QUARTER-TURN VALVES WITH 1/2" MIP/SWEAT CONNECTION, 3/8" O.D. COMPRESSION OUTLETS. VALVES COMPLY WITH ASME A112.18.1. USE 699-A1EMR WITH EXTENDED VALVE FOR THICKER WALLS. USE 699RF FOR WHITE ESCUTCHEON OR 699-FC FOR CHROME-PLATED ESCUTCHEON. USE 699RA1-MR WHEN INSTALLED IN FIRE-RATED WALLS.	–	699-A1-MR
					699RA1-MR
	TMV-1	THERMOSTATIC MIXING VALVE OUTLET BOX	SIOUX CHIEF 696-T2001PR OXBOX THERMOSTATIC MIXING VALVE OUTLET BOX WITH 1/2" MALE SWEAT INLET CONNECTION, INTEGRAL ISOLATION VALVES, INTERNAL CHECK VALVE AND STAINLESS STEEL MESH DEBRIS SCREEN. ASSE 1070 COMPLIANT. USE 696-1F FRAME. FLUSH SUPPLY LINES AT START UP. CAPABLE OF 1.6 GPM WITH A 20 PSI DIFFERENTIAL AND A MINIMUM FLOW RATE OF 0.25 GPM. SET TEMPERATURE TO 110F FOR DUAL TEMPERATURE LAVATORIES AND HAND SINKS, 100F FOR SINGLE TEMPERATURE LAVATORIES AND HAND SINKS. MOUNT BELOW THE PLUMBING FIXTURE WHERE INDICATED ON PLAN(S). USE 696RT2001PF WHEN INSTALLED IN FIRE-RATED WALLS. USE 120-TM3F FOR WALL-MOUNT APPLICATIONS (NO OUTLET BOX INCLUDED).	–	696-T2001PR
					696RT2001PF
					120-TM3F
	AAV-1	AIR ADMITTANCE VALVE AND OUTLET BOX	SIOUX CHIEF 250-696122P TURBOVENT AIR ADMITTANCE VALVE WITH DUAL FIT ADAPTER FOR 1-1/2" AND 2" VENT PIPE WITH OXBOX KIT. MEETS ASSE 1050 & 1051. ABS HOUSING AND ACTUATING DEVICE WITH ELASTROMERIC SEALING MEMBRANE AND PVC CONNECTOR, 2" INLET AND ATMOSPHERIC PORT. USE 250-696R122P WHEN INSTALLED IN FIRE-RATED WALLS.	2"	250-696122P
					250-696R122P
	GOB-1	GAS VALVE OUTLET BOX	SIOUX CHIEF 696-1021GF OXBOX GAS OUTLET BOX WITH 1/2" NPT VALVE AND ADAPTER FOR BLACK IRON PIPE. USE 696R1021GF FOR FIRE-RATED WALLS. USE 696-1031GF FOR 3/4" NPT VALVE.	–	696-1021GF
			1/2" NPT VALVE & ADAPTER FIRE-RATED 696R1021GF	–	696R1021GF
			3/4" NPT VALVE & ADAPTER 696-1031GF	–	696-1031GF
			3/4" NPT VALVE & ADAPTER FIRE-RATED 696R1031GF	–	696R1031GF
	WSB-1	WATER SERVICE SHUTOFF VALVE OUTLET BOX	SIOUX CHIEF 687-3PD SERVICEBOX WATER SERVICE SHUTOFF VALVE ACCESS BOX. 600WOG, BRASS 1/4-TURN VALVE WITH CAPPED DRAIN-DOWN PORT AND ANODIZED ALUMINUM T-HANDLE. 3/4" MSWT/PRESS/PUSH INLET AND OUTLET CONNECTION. USE 687-1F FRAME. APPROVED FOR USE IN FIRE-RATED WALLS.	–	687-2PD (1/2")
				–	687-3PD (3/4")
				–	687-4PD (1")
				–	687-5PD (1-1/4")
	PRV-1	PRESSURE REDUCING VALVE OUTLET BOX	SIOUX CHIEF 687-3RWWD SERVICEBOX PRESSURE-REDUCING VALVE WITH CAPPED DRAIN-DOWN PORT AND ACCESS BOX. ADJUSTABLE VALVE IS FACTORY SET TO 60PSI. ASSE 1003 COMPLIANT. 3/4" F1960 PEX INLET AND OUTLET CONNECTION. USE 687-1F FRAME. APPROVED FOR USE IN FIRE-RATED WALLS.	–	687-3RWWD (3/4")
				–	687-4RWWD (1")
	WHB-1	WATER HEATER SERVICE VALVE OUTLET BOX	SIOUX CHIEF 687-3WH2 SERVICEBOX WATER HEATER SERVICE VALVE OUTLET BOX. 600WOG, BRASS 1/4-TURN VALVE ON COLD-SIDE WITH ANODIZED ALUMINUM T-HANDLE. 3/4" F1960 PEX WATER SUPPLY INLET/OUTLET CONNECTION AND 3/4" MIP WATER HEATER INLET/OUTLET CONNECTION. USE 687-1F FRAME. APPROVED FOR USE IN FIRE-RATED WALLS.	–	687-3WH2 (TERMINATION)
				–	687-3WH (FLOW-THROUGH)
	WHA	WATER HAMMER ARRESTER	SIOUX CHIEF 652-A HYDRARESTER, PISTON-TYPE WATER HAMMER ARRESTER WITH HARD DRAWN COPPER BODY, LUBRICATED, DUAL EPDM O-RING SEALS. ASSE 1010 CERTIFIED. PROVIDE SIZE "A", UNLESS SHOWN OTHERWISE ON PLANS. APPROVED FOR INSTALLATION AT ANY ANGLE. NO ACCESS PANEL REQUIRED.	–	652-A (1/2")
				–	652-AS (1/2")
				–	653-B (3/4")
				–	653-BS (3/4")
				–	654-C (1")
				–	654-CS (1")
				–	655-D (1")
				–	655-DS (1")
				–	656-E (1")
				–	656-ES (1")
				–	657-F (1")
				–	657-FS (1")
	TRIM	P-TRAPS	CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/4" WITH SHALLOW ESCUTCHEON	1-1/4"	240-0453C04
			CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/2" WITH SHALLOW ESCUTCHEON	1-1/2"	240-0463C04
			CHROME PLATED P-TRAP WITH CLEANOUT, 17-GA BRASS 1-1/4" INLET X 1-1/2" OUTLET P-TRAP WITH SHLW ESCUT	1-1/4" X 1-1/2"	240-0487C04
		GRID STRAINERS	1-1/4" x 8" WITH OVERFLOW 17-GA CHROME PLATED CAST BRASS BODY WITH TAILPIECE AND BRASS NUT	1-1/4"	290-20514C04
			1-1/4" WHEELCHAIR OPEN GRID STRAINER 17-GA CHROME PLATED CAST BRASS BODY WITH OFFSET TAILPIECE, OVERFLOW AND BRASS NUT	1-1/4"	290-20515C04
		SUPPLY STOPS	LOOSE KEY COMPRESSION ANGLE STOP, CHROME PLATED, 5/8" O.D. COMPRESSION X 3/8" O.D. COMPRESSION	–	134-G2C1CLK04
			1/2" CTS METAL SHALLOW ESCUTCHEONS CHROME	–	910-2PK2
			LAVATORY SUPPLY TUBE CHROME PLATED COPPER 3/8" O.D. X 12" LONG	–	283-S04112C00

Project Name:

Project No:

Project Date:

General Notes:

Supply Pipe Material:

DWV Pipe Material:

Design Rainfall Rate:

Revision Date:

siouxchief.com

Sioux Chief

Sioux Chief Manufacturing
14940 Thunderbird Rd
Kansas City, MO 64147